

# Air Cooled Chillers & Heat Pumps

## Compact-Y SM



THAEY 122-130



**ÜNTES**<sup>®</sup>  
**52**  
years

## Compact-Y SM

THAEY 122-130

-  Cooling capacity: 22,7-29,0 kW
-  Heating capacity: 23,5-34,0 kW



- SCOP up to 3,26
- A+ Energy Class

Packaged reversible air-cooled heat pumps with axial fans. Range with scroll hermetic compressors and R410A refrigerant gas.

### Construction features

- Compressor: hermetic, rotary scroll compressor, complete with thermal protection and casing heater for mod. 127-130.
- Water side heat exchanger: adequately insulated stainless steel plates, complete with antifreeze heater and water flow differential pressure switch.
- Air side heat exchanger: finned coil with copper pipes and aluminium fins, complete with protection grilles.
- Fan: external rotor axial type electric fans equipped with internal thermal protection and accident protection grilles.
- Control: microprocessor electronic control with Adaptive Function Plus logic.
- Structure: in galvanised and painted steel plate, complete with condensate drain pan.

### Models

- THAEY: heat pump unit.

### PUMP set up

- Pump unit complete with: circulator or electric circulation pump, membrane expansion tank, manual air vent valve, safety valve and pressure gauge.

### TANK & PUMP set up

- Pump unit complete with: inertial buffer tank, circulator or electric circulation pump, membrane expansion tank, manual air vent valve, automatic air vent valve, safety valve, and pressure gauge.

### Factory fitted accessories

- Soft-start device.
- Silenced set up.
- -10°C condensing control.
- Antifreeze heater on the buffer tank.
- Compressor casing heater (mod. 122).
- Unit base antifreeze heater for operation in heat pump mode at low outdoor air temperatures.
- Digital input for double set-point
- 4-20 mA analogue signal for shifting set-point.
- Low water set-point temperature.
- Copper/pre-painted aluminium or copper/copper coils.

### Separately supplied accessories

- Rubber anti-vibration mounts.
- -10°C condensing control.
- Water filter.
- 3-way valve for the production of domestic hot water.
- Outdoor air temperature probe for set-point compensation.
- Additional electrical resistance for heat pump, managed by regulation.
- Remote keypad with display.
- Clock board.
- Interfaces for serial communication with other devices.
- Serial converter (RS485/USB).
- Untes supervisors for unit monitoring and remote management.

THAEY MODEL		122	127	130
① Heating capacity	kW	23,5	30,3	34,0
① Absorbed power	kW	7,94	10,16	11,25
① C.O.P.		2,96	3,02	3,02
② Heating capacity	kW	24,0	30,9	34,5
② C.O.P.		3,75	3,80	3,72
③ Cooling capacity	kW	22,7	26,7	29,0
③ Absorbed power	kW	7,99	10,23	11,84
③ E.E.R.		2,84	2,64	2,45
④ Sound pressure	dB(A)	52	53	53
④ Silenced set up sound pressure	dB(A)	49	50	50
Scroll/step compressor	no.	1/1	1/1	1/1
Circuits	no.	1	1	1
Buffer tank water content	l	45	45	45
⑤ Circulator/standard electric pump nominal available head	kPa	64/131	61/116	57/112
Electrical supply	V-ph-Hz	400-3+N-50	400-3+N-50	400-3+N-50
DIMENSIONS AND WEIGHTS		122	127	130
L - PUMP width	mm	1.230	1.535	1.535
W - TANK & PUMP width	mm	1.522	1.822	1.822
H - Height	mm	1.280	1.510	1.510
P - Depth	mm	600	695	695
⑤ THAEY weight	kg	278	320	380

Data at the following conditions:


- ① Air: 7°C D.B. - 6°C W.B. - Water: 40/45°C.
- ② Air: 7°C D.B. - 6°C W.B. - Water: 30/35°C.
- ③ Air: 35°C - Water: 12/7°C.
- ④ In open field (Q = 2) at 5 m from the unit.
- ⑤ Weight refers to most complete set up.

Performance according to EN 14511:2013. Set up with electric pump.

SEASONAL ENERGY PERFORMANCE		122	127	130
THAEY MODEL SEASONAL PERFORMANCE IN HEATING MODE				
③ Pdesignh (EN 14825)	kW	24	32	36
③ SCOP (EN 14825)		3,21	3,26	3,19
④ $\eta_s$	%	125	127	125
④ Energy class		A+	A+	A+

③ In Average climatic conditions, low temperature application (35°C)

④ Seasonal energy efficiency: low temperature heating in Average climate (EU Regulations No.811/213 and No.813/2013)



# ÜNTEŞ®

52  
years

#### Export Sales Office

**Address:** 53. Cadde 1450. Sokak Ulusoy  
Plaza No: 9/50 Cukurambar, Ankara, Turkey  
**Email:** export@untes.com.tr  
T+90 (312) 287 91 00 F+90 (312) 284 91 00

#### Manufacturing Plant-1

Air Handling & Ventilations Systems,  
Fan Coil Systems  
Packaged Air Conditioning Systems  
**Address:** Istanbul Yolu 37.km  
Kahramankazan, Ankara, Turkey

#### Manufacturing Plant-2

Water Chiller and Heat Pumps  
**Address:** Istanbul Yolu 24.km Saraykoy, Ankara

www.untes.com



untesklima